

					(%)		(kg)	(cm <sup>2</sup> )	(cm)	(cm)				
			700 799	1.0	( 2.6)	72.1	412.5	48.0	6.1	2.7	3.0	4.0	2.0	2.0
			499	1.0	( 2.6)	70.6	408.0	38.0	6.3	3.2	2.0	6.0	2.0	7.0
			500 599	1.0	( 2.6)	70.4	317.5	34.0	4.2	2.5	2.0	6.0	2.0	7.0
			500 599	1.0	( 2.6)	71.4	317.0	45.0	4.7	3.4	2.0	6.0	1.0	5.0
			600 699	2.0	( 5.3)	72.2	449.0	54.0	5.2	2.3	2.0	6.0	2.0	6.0
			2400 2499	2.0	( 11.1)	75.8	458.8	63.5	8.8	2.1	7.0	5.0	4.5	3.0
			2300 2399	4.0	( 22.2)	74.0	432.0	54.3	7.7	2.4	4.0	4.8	3.0	3.0
			2200 2299	4.0	( 22.2)	73.8	403.1	50.8	7.3	2.2	4.0	5.0	2.8	3.3
			2100 2199	2.0	( 11.1)	73.0	421.5	46.5	8.0	2.8	4.0	5.0	3.0	3.0
			2000 2099	2.0	( 11.1)	72.3	447.5	52.5	7.2	3.5	3.0	5.0	2.0	3.0
			1900 1999	2.0	( 11.1)	73.6	351.8	45.0	7.0	2.1	3.5	4.5	3.0	2.5
			1600 1699	2.0	( 11.1)	70.8	376.3	37.0	6.4	3.3	2.5	5.0	2.0	3.5
				18.0	( 47.4)	73.5	414.0	50.5	7.5	2.6	4.0	4.9	2.9	3.1
			2500	2.0	( 28.6)	75.3	481.9	71.5	8.3	3.2	6.0	3.0	4.0	2.5
			2400 2499	1.0	( 14.3)	73.5	505.3	61.0	8.0	3.1	5.0	3.0	3.0	2.0
			2300 2399	2.0	( 28.6)	73.6	495.9	63.0	8.0	3.5	3.5	3.5	2.5	3.0
			2200 2299	1.0	( 14.3)	71.7	430.7	48.0	7.9	4.2	3.0	4.0	3.0	3.0
			1600 1699	1.0	( 14.3)	73.0	550.5	67.0	7.2	3.3	5.0	5.0	3.0	4.0
				7.0	( 18.4)	73.7	491.7	63.6	7.9	3.4	4.6	3.6	3.1	2.9
			700 799	1.0	( 14.3)	72.7	375.4	50.0	6.0	2.8	2.0	5.0	2.0	5.0
			600 699	4.0	( 57.1)	72.1	422.5	43.5	6.4	2.1	2.0	4.8	2.0	4.3
			500 599	2.0	( 28.6)	72.8	405.5	48.0	6.8	2.5	2.0	5.0	2.0	3.5
				7.0	( 18.4)	72.4	410.9	45.7	6.4	2.3	2.0	4.9	2.0	4.1
			2500	2.0	( 5.3)	75.3	481.9	71.5	8.3	3.2	6.0	3.0	4.0	2.5
			2400 2499	3.0	( 7.9)	75.1	474.3	62.7	8.5	2.4	6.3	4.3	4.0	2.7
			2300 2399	6.0	( 15.8)	73.8	453.3	57.2	7.8	2.8	3.8	4.3	2.8	3.0
			2200 2299	5.0	( 13.2)	73.4	408.6	50.2	7.4	2.6	3.8	4.8	2.8	3.2
			2100 2199	2.0	( 5.3)	73.0	421.5	46.5	8.0	2.8	4.0	5.0	3.0	3.0
			2000 2099	2.0	( 5.3)	72.3	447.5	52.5	7.2	3.5	3.0	5.0	2.0	3.0
			1900 1999	2.0	( 5.3)	73.6	351.8	45.0	7.0	2.1	3.5	4.5	3.0	2.5
			1600 1699	3.0	( 7.9)	71.6	434.3	47.0	6.7	3.3	3.3	5.0	2.3	3.7
			700 799	2.0	( 5.3)	72.4	393.9	49.0	6.0	2.8	2.5	4.5	2.0	3.5
			600 699	6.0	( 15.8)	72.1	431.3	47.0	6.0	2.2	2.0	5.2	2.0	4.8
			500 599	4.0	( 10.5)	71.9	361.4	43.8	5.6	2.8	2.0	5.5	1.8	4.8
			499	1.0	( 2.6)	70.6	408.0	38.0	6.3	3.2	2.0	6.0	2.0	7.0



[illegible]