

					(%)		(kg)	(m ²)	(m)	(m)				
			1800 1899	1.0	(0.4)	74.7	491.0	64.0	8.6	2.9	6.0	5.0	4.0	3.0
			1700 1799	1.0	(20.0)	72.4	424.0	54.0	7.3	4.0	5.0	3.0	4.0	2.0
			1500 1599	1.0	(20.0)	70.3	528.0	39.0	9.6	4.4	3.0	5.0	3.0	2.0
			1400 1499	1.0	(20.0)	74.7	507.0	69.0	8.2	3.2	3.0	5.0	2.0	3.0
			1300 1399	1.0	(20.0)	75.2	375.0	61.0	6.7	2.1	3.0	4.0	2.0	2.0
			800 899	1.0	(20.0)	70.6	334.0	31.0	4.6	1.9	2.0	6.0	2.0	6.0
				5.0	(2.0)	72.6	433.6	50.8	7.3	3.1	3.2	4.6	2.6	3.0
			2100 2199	1.0	(7.7)	75.7	550.4	82.0	7.8	3.0	4.0	4.0	3.0	3.0
			1800 1899	1.0	(7.7)	72.3	478.2	56.0	7.5	3.8	3.0	5.0	2.0	3.0
			800 899	1.0	(7.7)	71.3	398.5	37.0	6.6	2.6	2.0	4.0	2.0	4.0
			500 599	6.0	(46.2)	71.9	356.1	34.8	5.8	1.7	2.3	4.5	1.8	6.3
			499	4.0	(30.8)	71.8	403.4	37.3	6.0	1.6	2.3	4.5	2.0	6.8
				13.0	(5.1)	72.1	398.2	41.0	6.2	2.0	2.5	4.5	2.0	5.8
			600 699	1.0	(0.4)	71.1	337.0	36.0	5.3	2.6	2.0	6.0	2.0	5.0
			1400 1499	1.0	(33.3)	71.3	401.5	40.0	5.7	2.3	2.0	5.0	2.0	4.0
			1300 1399	1.0	(33.3)	72.4	394.5	44.0	5.5	1.6	2.0	5.0	2.0	4.0
			1100 1199	1.0	(33.3)	72.8	365.2	44.0	7.0	2.7	2.0	5.0	2.0	3.0
				3.0	(1.2)	72.2	387.1	42.7	6.1	2.2	2.0	5.0	2.0	3.7
			1000 1099	1.0	(25.0)	71.2	290.4	37.0	4.1	2.3	2.0	5.0	2.0	3.0
			900 999	3.0	(75.0)	72.3	272.7	41.3	4.0	1.9	2.0	4.7	1.7	5.0
				4.0	(1.6)	72.0	277.1	40.3	4.0	2.0	2.0	4.8	1.8	4.5
			2500	23.0	(12.8)	74.9	441.2	57.8	8.2	2.2	6.2	4.2	4.1	2.9
			2400 2499	16.0	(8.9)	74.5	428.3	54.1	7.8	2.0	5.1	4.3	3.6	2.9
			2300 2399	28.0	(15.6)	74.2	421.1	52.9	7.6	2.1	4.6	4.6	3.3	3.0
			2200 2299	21.0	(11.7)	74.1	423.8	51.0	8.0	2.3	4.2	4.5	3.1	3.0
			2100 2199	24.0	(13.3)	73.6	413.7	50.5	7.4	2.4	3.6	4.6	2.8	2.9
			2000 2099	22.0	(12.2)	73.9	409.0	50.5	7.3	2.1	3.2	4.7	2.4	3.1
			1900 1999	12.0	(6.7)	73.2	404.2	46.8	7.1	2.2	3.1	4.8	2.3	3.0
			1800 1899	8.0	(4.4)	72.8	428.8	46.6	7.1	2.3	2.5	4.9	2.0	3.4
			1700 1799	1.0	(0.6)	71.7	331.5	34.0	5.2	1.6	2.0	5.0	2.0	4.0
			1600 1699	2.0	(1.1)	71.8	396.3	44.0	6.2	2.8	2.5	5.0	2.0	3.5
			1500 1599	1.0	(0.6)	75.2	374.5	56.0	6.7	1.4	2.0	5.0	2.0	3.0
			1300 1399	1.0	(0.6)	71.1	345.0	34.0	5.9	2.7	2.0	5.0	2.0	4.0
			1200 1299	2.0	(1.1)	72.6	336.0	38.0	5.4	1.3	2.0	5.0	2.0	4.0
			1100 1199	2.0	(1.1)	73.3	359.3	50.5	5.0	1.6	2.0	5.5	2.0	3.5
			1000 1099	3.0	(1.7)	72.8	368.2	45.7	5.4	1.7	2.0	5.7	1.7	3.3
			800 899	4.0	(2.2)	72.0	370.5	42.0	5.2	1.9	2.3	5.3	1.3	4.5

[illegible]