

					(%)		(kg)	(cm <sup>2</sup> )	(cm)	(cm)				
			1500 1599	1.0	( 25.0)	73.0	520.3	66.0	9.2	2.7	8.0	4.0	5.0	3.0
			1200 1299	2.0	( 50.0)	70.6	474.0	50.5	8.1	3.1	4.0	4.0	3.5	3.0
			600 699	1.0	( 25.0)	71.9	305.0	50.0	4.6	1.3	2.0	6.0	2.0	4.0
				4.0	( 22.2)	71.5	443.3	54.3	7.5	2.5	4.5	4.5	3.5	3.3
			1500 1599	1.0	( 50.0)	73.1	392.0	57.0	7.3	1.8	8.0	4.0	5.0	2.0
			1200 1299	1.0	( 50.0)	71.8	367.0	51.0	6.4	2.1	3.0	4.0	3.0	3.0
				2.0	( 11.1)	72.5	379.5	54.0	6.8	1.9	5.5	4.0	4.0	2.5
			1000 1099	1.0	( 25.0)	68.0	525.0	36.0	7.5	2.8	3.0	5.0	2.0	3.0
			700 799	1.0	( 25.0)	66.8	485.5	37.0	5.2	3.1	3.0	5.0	2.0	4.0
			500 599	1.0	( 25.0)	68.6	420.5	38.0	5.6	2.5	2.0	5.0	2.0	4.0
			499	1.0	( 25.0)	70.8	464.0	48.0	6.7	1.6	3.0	6.0	2.0	4.0
				4.0	( 22.2)	68.5	473.8	39.8	6.3	2.5	2.8	5.3	2.0	3.8
			1900 1999	1.0	( 5.6)	75.2	472.0	82.0	8.6	3.0	11.0	4.0	5.0	3.0
			1500 1599	1.0	( 50.0)	73.0	446.0	68.0	6.7	2.3	7.0	3.0	4.0	3.0
			1200 1299	1.0	( 50.0)	71.8	466.0	55.0	7.7	2.2	3.0	4.0	2.0	3.0
				2.0	( 11.1)	72.4	456.0	61.5	7.2	2.3	5.0	3.5	3.0	3.0
			1000 1099	1.0	( 5.6)	69.4	359.6	43.0	6.2	3.5	4.0	4.0	3.0	3.0
			2000 2099	1.0	( 33.3)	75.6	457.3	78.0	8.5	2.1	10.0	3.0	5.0	3.0
			1300 1399	1.0	( 33.3)	69.7	443.0	47.0	7.6	3.7	3.0	5.0	3.0	3.0
			1100 1199	1.0	( 33.3)	71.2	450.0	51.0	7.8	2.6	4.0	4.0	3.0	3.0
				3.0	( 16.7)	72.2	450.1	58.7	8.0	2.8	5.7	4.0	3.7	3.0
			1500 1599	1.0	( 5.6)	70.6	389.5	52.0	6.8	3.6	8.0	4.0	5.0	3.0
			2000 2099	1.0	( 5.6)	75.6	457.3	78.0	8.5	2.1	10.0	3.0	5.0	3.0
			1900 1999	1.0	( 5.6)	75.2	472.0	82.0	8.6	3.0	11.0	4.0	5.0	3.0
			1500 1599	4.0	( 22.2)	72.4	436.9	60.8	7.5	2.6	7.8	3.8	4.8	2.8
			1300 1399	1.0	( 5.6)	69.7	443.0	47.0	7.6	3.7	3.0	5.0	3.0	3.0
			1200 1299	4.0	( 22.2)	71.2	445.3	51.8	7.5	2.6	3.5	4.0	3.0	3.0
			1100 1199	1.0	( 5.6)	71.2	450.0	51.0	7.8	2.6	4.0	4.0	3.0	3.0
			1000 1099	2.0	( 11.1)	68.7	442.3	39.5	6.8	3.1	3.5	4.5	2.5	3.0
			700 799	1.0	( 5.6)	66.8	485.5	37.0	5.2	3.1	3.0	5.0	2.0	4.0
			600 699	1.0	( 5.6)	71.9	305.0	50.0	4.6	1.3	2.0	6.0	2.0	4.0
			500 599	1.0	( 5.6)	68.6	420.5	38.0	5.6	2.5	2.0	5.0	2.0	4.0
			499	1.0	( 5.6)	70.8	464.0	48.0	6.7	1.6	3.0	6.0	2.0	4.0
				18.0	(100.0)	71.2	439.5	53.3	7.1	2.6	5.0	4.3	3.3	3.2

					(%)		(kg)	(cm <sup>2</sup> )	(cm)	(cm)				
			1600 1699	3.0	( 21.4)	71.1	533.3	54.7	8.2	2.5	7.7	4.0	4.3	3.0
			1500 1599	1.0	( 7.1)	71.2	629.5	58.0	9.5	2.4	8.0	3.0	5.0	3.0
			1400 1499	1.0	( 7.1)	70.8	564.0	55.0	8.8	2.8	6.0	4.0	4.0	3.0
			1300 1399	1.0	( 7.1)	72.8	507.0	67.0	8.0	2.5	3.0	3.0	3.0	3.0
			1200 1299	4.0	( 28.6)	70.8	530.2	57.5	8.1	3.1	6.0	4.3	4.3	3.0
			1000 1099	2.0	( 14.3)	71.3	542.7	57.0	8.0	2.3	3.0	4.0	2.5	3.0
			900 999	2.0	( 14.3)	70.3	421.0	42.0	7.1	2.3	2.5	3.5	2.0	2.5
				14.0	( 0.9)	71.0	524.9	55.1	8.1	2.6	5.4	3.9	3.6	2.9
			1100 1199	1.0	( 0.1)	70.2	432.2	41.0	7.0	2.0	5.0	4.0	4.0	2.0
			1400 1499	1.0	( 0.1)	71.2	432.5	53.0	7.8	3.1	6.0	4.0	4.0	3.0
			1400 1499	1.0	( 0.1)	70.2	431.0	49.0	6.9	3.0	3.0	4.0	3.0	3.0
			1600 1699	1.0	( 0.1)	72.6	610.0	73.0	9.4	3.2	7.0	5.0	4.0	3.0
			1900 1999	31.0	( 8.2)	72.3	510.9	61.9	8.6	2.7	5.1	4.1	3.6	2.8
			1800 1899	128.0	( 34.0)	71.0	525.6	56.4	8.5	3.2	3.6	4.1	3.0	2.8
			1700 1799	157.0	( 41.8)	70.6	531.1	55.3	8.2	3.1	3.0	4.3	2.1	2.7
			1600 1699	60.0	( 16.0)	69.0	556.0	50.4	8.4	4.0	2.5	4.7	2.0	2.5
				376.0	( 23.5)	70.6	531.5	55.4	8.4	3.2	3.3	4.3	2.5	2.7
			1900 1999	13.0	( 7.3)	71.5	536.2	58.2	8.7	2.9	5.5	3.9	3.7	2.6
			1800 1899	83.0	( 46.4)	70.4	528.0	54.7	8.3	3.3	3.9	4.0	3.0	2.7
			1700 1799	68.0	( 38.0)	69.7	519.7	50.8	8.1	3.6	3.0	4.2	2.2	2.5
			1600 1699	15.0	( 8.4)	68.5	522.6	47.1	7.7	4.0	2.6	4.5	2.0	2.3
				179.0	( 11.2)	70.1	525.0	52.8	8.2	3.4	3.6	4.1	2.7	2.6
			1800 1899	6.0	( 14.0)	69.4	525.9	49.2	8.5	3.8	3.7	4.0	3.0	2.8
			1700 1799	23.0	( 53.5)	69.6	552.9	50.7	8.8	3.7	3.0	4.2	2.1	3.0
			1600 1699	14.0	( 32.6)	67.8	563.1	44.9	9.0	4.8	2.6	4.4	2.0	3.0
				43.0	( 2.7)	69.0	552.4	48.6	8.8	4.1	3.0	4.2	2.2	3.0
			2000 2099	4.0	( 0.4)	72.2	574.0	65.8	9.0	2.8	6.5	4.0	4.3	3.0
			1900 1999	95.0	( 9.6)	71.2	562.1	61.2	8.8	3.3	5.5	4.1	3.8	2.9
			1800 1899	402.0	( 40.7)	70.3	558.2	55.9	8.7	3.5	3.9	4.1	3.0	2.9
			1700 1799	346.0	( 35.1)	69.3	559.7	52.6	8.5	3.9	3.1	4.3	2.4	2.9
			1600 1699	140.0	( 14.2)	68.2	559.9	48.2	8.3	4.5	2.7	4.6	2.0	2.8
				987.0	( 61.6)	69.8	559.4	54.2	8.6	3.8	3.6	4.3	2.7	2.9
			2000 2099	4.0	( 0.2)	72.2	574.0	65.8	9.0	2.8	6.5	4.0	4.3	3.0
			1900 1999	139.0	( 8.7)	71.5	548.3	61.1	8.7	3.1	5.4	4.1	3.8	2.9

